



Enduring Quality, Exceptional Value

[www.marathonbroadband.com](http://www.marathonbroadband.com)

# Natural and UV Black Nylon 6.6 Cable Ties

- Great for bundling cable, wire, hoses, ducts and countless other applications
- Good resistance to bases, oils, grease, oil derivatives and chloride solvents
- Flammability rating: UL 94 - V2
- UL Certified for electrical installations under UL62275
- UL Certified to support flexible metal conduits and cables in construction under UL Type 21
- Min/Max Operating Temp: -40°F/185°F (-40°C/85°C)
- Min Install Temp: 14°F (10°C)



## Natural RoHS and Reach Compliant, Not UV Resistant | Plastic Barb Type

Part Number	SIM Number	UL Reference #	Pack Size	Length		Tensile Strength		Min Bundle Diameter		Max Bundle Diameter	
				in.	mm	lbs.	N	in.	mm	in.	mm
CTNAT5IN401000	40156499959	LH-I-140-5-AH	1,000	5.5	140	40	180	0.14	3.5	1.3	33.0
CTNAT8IN501000	40156499960	LH-S-190-8-AH	1,000	7.5	190	50	230	0.14	3.5	1.8	46.0
CTNAT8IN50100	40156499954	LH-S-200-8-AH	100	8.0	200	50	230	0.14	3.5	2.0	49.5
CTNAT8IN401000	40156499964	LH-I-200-8-AH	1,000	8.0	200	40	180	0.14	3.5	20.7	52.5
CTNAT8IN181000	40156499962	LH-M-200-8-AH	1,000	8.0	200	18	80	0.14	3.5	2.1	52.5
CTNAT15IN50100	40156499968	LH-S-370-15-AH	100	14.5	370	50	230	0.14	3.5	3.9	100.0

## High Performance Black, UV Resistant | Metal Barb Type

Part Number	SIM Number	UL Reference #	Pack Size	Length		Tensile Strength		Min Bundle Diameter		Max Bundle Diameter	
				in.	mm	lbs.	N	in.	mm	in.	mm
CTBHP8IN501000	40156499965	LH-S-200-8-LST-UVB	1,000	8.0	200	50	230	0.14	3.5	49.5	49.5
CTBHP12IN401000	40156499970	LH-300-12-LST-UVB	1,000	11.8	300	40	180	0.14	3.5	3.3	84.0
CTBHP15IN501000	40156499972	LH-S-370-15-LST-UVB	1,000	14.5	370	50	230	0.14	3.5	4.4	103.5

Marathon products are available from the following distributors:

**Wesco**  
buy.wesco.com  
866.746.3519

**Anixter**  
Anixter.com  
866.746.3519

221825D001  
D231220-VF



Enduring Quality, Exceptional Value

[www.marathonbroadband.com](http://www.marathonbroadband.com)



Standard Black RoHS and Reach Compliant, UV Resistant | Plastic Barb Type

Part Number	SIM Number	UL Reference #	Pack Size	Length		Tensile Strength		Min Bundle Diameter		Max Bundle Diameter	
				in.	mm	lbs.	N	in.	mm	in.	mm
CTB4IN181000	40156499958	LH-M-100-4-UVB	1,000	4.0	100	18	80	0.12	3.4	0.8	20.5
CTB5IN401000	40156499963	LH-I-140-5-UVB	1,000	5.5	127	40	180	0.14	1.3	3.5	33.0
CTB8IN40100	40156499957	LH-I-200-8-UVB	100	8.0	200	40	180	0.14	3.5	2.1	52.5
CTB8IN50100	40156499953	LH-S-200-8-UVB	100	8.0	200	50	230	0.14	3.5	2.0	49.5
CTB8IN120100	40156499950	LH-HD-200-8-UVB	100	8.0	200	120	540	0.33	8.5	2.0	50.9
CTB8IN501000	40156499967	LH-S-190-8-UVB	1,000	8.0	203	50	230	0.14	1.7	3.0	46.0
CTB11IN40100	40156499956	LH-I-280-11-UVB	100	11.0	280	40	180	0.14	3.5	3.1	78.0
CTB11IN50100	40156499952	LH-S-280-11-UVB	100	11.0	280	50	230	0.14	3.5	3.2	81.0
CTB12IN501000	40156499961	LH-S-300-12-UVB	1,000	11.8	300	50	230	0.14	3.5	3.2	81.0
CTB14IN50100	40156499951	LH-S-360-14-UVB	100	14.0	360	50	230	0.14	3.5	3.9	100.0
CTB14IN120100	40156499949	LH-HD-365-14-UVB	100	14.0	365	120	540	0.33	8.5	4.1	104.1
CTB15IN40100	40156499955	LH-I-370-15-UVB	100	14.5	370	40	180	0.14	3.5	4.2	106.7
CTB15IN50100	40156499971	LH-S-370-15-UVB	100	14.5	370	50	230	0.14	3.5	4.4	111.8
CTB15IN50500	40156499966	LH-S-370-15-UVB	500	14.5	370	50	230	0.14	3.5	4.4	111.8
CTB15IN501000	40156499969	LH-S-370-15-UVB	1,000	14.5	370	50	230	0.14	3.5	3.9	103.5

Marathon products are available from the following distributors:

**Wesco**  
[buy.wesco.com](http://buy.wesco.com)  
 866.746.3519

**Anixter**  
[Anixter.com](http://Anixter.com)  
 866.746.3519

221825D001  
 D231220-VF